



Telehandler / Zoom Boom

Used Telehandler Riverside - Telehandlers are commonly known by a variety of names such as Cherry pickers, telescopic handlers, boom lifts and teleporters. This industrial machine is commonly used in a variety of industries and in agriculture. This machine functions similarly to a crane and a forklift with the ability to extend upward and forward. Many different attachments can be used at the end of the articulating boom to facilitate a wide number of jobs. Common attachments include pallet forks, a winch, a bucket or a muck grab. The most common telehandler attachment is the pallet forks. These attachments help the operator transport different sized loads to many locations that would be considered unreachable with a traditional forklift. These machines enable cargo pallets to be unloaded and loaded from a trailer and placed on rooftops, racking or other high and hard to access locations. Often, high rooftop locations would need a crane although, telehandlers can accomplish these tasks much more efficiently. Of course, it isn't always affordable or practical to use secondary equipment or a crane to complete certain tasks. A bucket or bucket grab is the most popular telehandler attachment in the agricultural industry. Relocating items from hard to reach areas that cannot rely on a wheeled loader or a backhoe loader give telehandlers a significant advantage. For instance, these industrial machines can directly access a hopper or trailer with high sides; applications that would otherwise rely on a conveyor, loading ramp or similar equipment. Using one machine to finish numerous jobs saves storage space, money and time. Telehandler units often work together with a crane jib. Various attachments may be used including rotators, dirt buckets, grain buckets and power booms. Agricultural models can be outfitted with power take-off and 3-point linkage, making the telehandler and exceptionally useful. Conversely, the main advantage of this machine doubles as its' largest limitation. When raising or extending with heavy loads, the boom functions similar to a lever. Despite significant counterweights in the rear, the telehandler can be subject to instability at times, decreasing the lifting capacity as the working radius or distance between the center of the load and the front of the wheels increases. If the machine works as a single boom loader instead of using twin arms while carrying a large load, there is a chance that weakness can occur even in the most carefully designed units. A 5000 lb. capacity telehandler could lift 400 lbs. safely while fully extended with a retracted boom in conjunction with a low boom angle. Raising the same piece of equipment 70 degrees could allow this machine with a five thousand pound lift capability and retracted boom to support up to ten thousand pounds. These machines are equipped with a load chart to help outline which tasks are safely possible. These charts take the boom height, angle and weight into account. There are sensors and computers available on newer models. The operator is warned and even cut off further control input once the limits of the telehandler are surpassed. There are front stabilizers that can drastically enhance the machine's lifting capacity while it is stationary. A mobile crane can also use a bucket is another option consisting of a stabilized rotary joint found between upper and lower frames. There are compact telehandler models that differ in boom design, size, reach and weight. Telehandlers fall into the compact category if the unit weighs in at 11,000 lbs. or less. Compact models feature a two- stage boom design in comparison to the three or four boom design that is common with larger units. Compact models rely on a low pivot boom to facilitate better cab visibility as the operator transports loads. There are narrower and smaller dimensions offered with the compact telehandler. The compact units offer a reach capacity between thirteen to twenty feet and a lifting capacity ranging from five thousand to seven thousand pounds. There are many different applications this machine is suitable for working in. This machine can be utilized for carrying tools or as a pick and place unit. Compact units are ideal for cramped locations. It is common for contractors to use this machine during framing and for residential jobs where there are height restrictions. These machines can facilitate internal building access. Compact telehandlers are commonly used in nurseries, landscaping, multi-story construction, building strip malls and garages, masonry, erecting steel and more. Farming and agri-business applications often rely on telehandlers to accomplish many tasks. Telehandlers are made with two or

four-wheel drive as well as crab steering. This machine can traverse longer distances with two-wheel drive at higher speeds to facilitate easy travel between worksites. The 4-WD units are capable of having a tighter turning radius and can travel difficult terrain. Crab steering is responsible for the increased maneuverability, allowing the front and rear wheels to shift forty-five degrees to the right or left. There are a variety of cab interior options available for compact telehandlers. On the lower-end models, a rollover protective cage structure is in place for safety. Higher-end models are equipped with a fully enclosed cab, a heater, windshield wiper and defroster. All compact telehandler cabs are spacious to accommodate the operator as comfortable as possible. Additional options including satellite radio, air conditioning, armrests, cup holders, suspension seats and tilt steering are available. The numerous attachment options are facilitated with high-pressure and high-flow auxiliary hydraulics. The different attachments allow the machine to be capable of many options. All of these attachments enable the machine to conduct a variety of jobs. Ground engaging work is often completed by compact units. It is simple to transform a compact telehandler into a mini excavator with a bucket attachment. There are popular attachments including brooms for sweeping, truss booms for extended reach, side-shifting and rotating fork carriages, heavy and light-duty buckets, augers for planting trees or digging holes and many items. Skid steer attachments are being manufactured for certain compact telehandler designs for even more versatility.